

ISOBELL® STUCCO

Acrylic adhesive/skim coat
READY- TO-USE PASTA

PRODUCT DESCRIPTION

Adhesive/skim coat paste ideal for treating cracked walls exposed to bad weather. It is an extremely elastic system with dynamic characteristics that last over time.

COMPOSITION

Synthetic resin aqueous emulsion with adhesion accelerators, single-size aggregate, lightened with perlite and different additives. One-millimeter grain paste coating made out of acrylic binder. Extremely water repellent, and highly workable.

CONSUMPTION

1,5 – 2 kg/m² to glue on the wall with a 4/5 mm notched trowel ;
2- 2,5 kg/m² for skimming with two coats.

DRYING

Dry to touch 6 hours
Dry deep down 48-60 hours

data with 20° C and 65% R.H.) drying time depends strictly on the conditions of humidity and temperature



MANIFATTURA DEL SEVESO S.p.A

Via: Vespucci, 20 | 24046 Osio Sotto (BG)

T: +39 035 881950 | www.isobell.it | info@isobell.it

 **MADE IN ITALY**

DATA SHEET

USE

Bases to be treated must be intact, without parts that are breaking off, free from substances that could hinder the system's adhesion (oil, grease), and dry; humidity may cause the covering to come off. Synthetic self-adhesive plastic mixture to be used as is when setting the ISOBELL course in place. You can also use it as a finish or as a skim coat for drowning the mesh.

BASE

Ideal for outdoors, wherever you want to make improvements on deteriorating walls and façades. You can put it on any type of plaster. The surface has to be dry without any dirt or dust on it. Any mold or algae must be treated beforehand with suitable disinfecting products.

APPLICATION

After having mixed the material, you can use it right away. If necessary, adjust the mixture with water until it gets to the right working consistency. Used as reinforcement mortar or finishing mortar to correct the uneven spots on all bases with minerals and organic substances on them. Do not use on wet bases. Apply the adhesive to the base to be treated with a comb, aiming to attain consumption of about 1.5/2 kg/m². Then install the ISOBELL® course. Once you're done with installation, skim it with a plastic filling knife. When outside, you have to lay on an extra coat of the ISOBELL® STUCCO product before installing the covering and you can put an 80 g, 100-mm wide fiberglass gauze on the joints of each insulation panel.

CHARACTERISTICS

Ultrahydrophobicity: the product's special formula protects from the weather, creating an uninterrupted "skin" that stops rain from getting in, thus keeping the walls dry.

Workability: the adhesive/skim coat's thixotropy is very smooth-flowing and adheres well to the base to limit material detachment during installation.

Protection from mold and algae thanks to the special anti-mold additives guarantees a high level of protection.

STORAGE

Twelve months in the well-sealed original containers and stored indoors, away from direct sunlight at a temperature from +5°C to +35°C.

PROTECT FROM FROST

PACKAGES: 20 kg