ISOBELL PURE+

Anti-mould cleaner for wall surfaces

TECHNICAL DATA SHEET issue date: 14/10/2026 Rev.2

PRODUCT DESCRIPTION

Professional cleaner for walls and wall surfaces affected by mould, algae and fungi, before ISOBELL restoration cycles.

COMPOSITION

Aqueous emulsion containing active additives against fungi, algae and mould.

APPLICATION CONDITIONS

Temperature: 8 - 30°C;
Relative humidity: max 80%

APPEARANCE

Low-viscosity, milky, colourless liquid, fully soluble in water.



DILUTION and pH

pH 13 . Ready to use DO NOT DILUTE

CONSUMPTION

7-10 m^2/l depending on the porosity of the substrate.

Coverage may vary depending on the unevenness of the surfaces to be treated.

DRYING

Through dry 24-48 hours
Recoating 2-3 hours

Data refer to 20° C and 65% R.H.; drying times depend closely on the conditions of moisture and temperature.

STORAGE AND MIXING

Keeps for 12 months in the original, tightly closed containers stored indoors, away from direct sunlight, at a temperature between + 8° C and + 35° C. Protect from frost. Do not mix with other products. Any mixing alters the properties and quality of the product.

PACKAGING

1 Litre - 6 containers in a cardboard box, 6 litres in total

METHODS AND TOOLS

Apply by brush, roller or spray. Clean with water immediately after use.

ISOBELL
LIVE YOUR COMFORT

USE

Mould on walls is a common problem in many homes. PURE+ is the cycle developed to remove mould from wall surfaces before the ISOBELL treatment, in compliance with the safety instructions on the label.

Biocides are essential to combat organisms harmful to human and animal health and to prevent the deterioration of natural or manufactured materials. However, they must be used responsibly to avoid environmental and health risks.

For example, water used to wash equipment must not be discharged into the soil or surface water, to prevent contamination. In addition, containers with product residues must be disposed of in compliance with current regulations, through authorised channels.

Use biocides safely. Always read the label and product information before use.

APPLICATION

Apply the product directly to the surfaces to be treated with a brush or roller, making sure to cover the area evenly. Leave the product to act for a few hours, respecting the times stated on the label.

Then carefully remove any unwanted efflorescence by cleaning or brushing. Then paint using specific anti-mould and anti-algae products.

Note that the product, as a biocide, acts during application and until it is completely dry. The stated drying times must be respected to allow the product to act effectively against mould, algae and microorganisms. Do not paint while the product is still damp, to avoid interference between the active biocides and the finishing paint.

Finally, as the substrate may be weakened by the treatment, it is advisable not to wait too long before applying the finishing coats, to ensure an optimal result and longer durability of the work.

WARNINGS

- Do not mix with chlorine-based products and do not apply chlorine-based products.
- Given the high alkalinity of the product, carefully cover all surfaces adjacent to the one to be painted, especially glass, ceramics, bricks, etc., to avoid damage.

- Do not apply in rain, threat of rain, on façades in direct sun (use sheeting on scaffolding) or in strong wind.
- Do not apply on wet or damp substrates with a concentration above 85%
- Do not apply on frozen or thawing substrates.
- The use of skilled labour is recommended.
- Use as supplied, without adding foreign materials.

The information and instructions above, although based on our best experience, are in all cases purely indicative and must be confirmed by thorough practical applications; therefore, before using the product, the user must establish whether it is suitable for the intended use and, in any case, assumes all liability arising from its use.

WATER-BASED

SOLVENT-FREE

ISOBELL

LIVE YOUR COMFORT

SPECIFICATION TEXT

PURE+

Anti-mould treatment with the PURE+ system

Specific treatment to remove mould from interior or exterior wall surfaces, including:

Preliminary cleaning of the substrate and removal of efflorescence.
Application of PURE+ biocide by brush or roller, respecting the drying times for the product to act fully.
Finish with two coats of specific anti-mould and anti-algae paint.
Containers and residues must be disposed of correctly in accordance with current regulations.

LEGAL NOTICE

The contents of this Technical Data Sheet may be reproduced in another design document, but the resulting document may in no way replace or supplement the Technical Data Sheet in force at the time the ISOBELL product is applied.

The latest Technical Data Sheet is available on our website www.isobell.it.

ANY ALTERATION OF THE TEXT OR CONDITIONS IN THIS TECHNICAL DATA SHEET OR ARISING FROM IT EXCLUDES THE LIABILITY OF MANIFATTURA DEL SEVESO.

WATER-BASED

SOLVENT-FREE

Manifattura del Seveso Spa
Via A.Vespucci 20
24046 Osio Sotto BG
info@isobell.it
www.isobell.it

EN 13984:2013

MADE IN ITALY